

Virtual Wall

LED All-in-one Display Terminal



PRODUCT FEATURES



**Industry-level System
Reliable and User-friendly
Operation**

Industry-level system brings stable and reliable product performance. Control via mobile devices makes interaction more efficient.

Screen control via mobile device¹

Self-developed APPs



**Ultra High Definition
Versatile Application Modes**

Ultra-HD display effect ensures perfect viewing experience without loss of detail. Built-in video processing function supports screen splitting mode and easy switch.

4K@60Hz²

Various Scene Modes³

High gray scale level under low brightness



**Highly Integrated Design
Audio-visual All-in-one
Experience**

Built-in high quality audio system tuned by professional sound engineer and fully upgraded audio analytic algorithm provides immersive all-round enjoyment.

Professional Sound System

90DB Sensitivity

180Hz-20KHz Frequency Response

2*30W Speakers



**Elegant & Decent Product
Appearance**

New fabric cover design enables the product to fit in different application scenarios. Highly integration both on hardware and control system ensure more stable performance.

Fabric Cover

Sound Filtering & Dustproof

Adaptive Brightness⁴

Type-C Port⁵



1. Install APP called LedConfig on mobile phone and tablet PC to control the LED all-in-one display terminal;
2. The HDMI 2.0 are used as external input and output ports, supporting 4K@60Hz signal input and output;
3. The display terminal has built-in scene modes, including meeting mode, display mode, power-saving mode and user mode;
4. Screen brightness can be adjusted automatically according to ambient light change;
5. Front Type-C port can match Type-C USB flash drive.

SPECIFICATIONS

Display Diagonal (inches)	138"	138"	165"	220"	120"	120"	150"	180"
Overall Dimension (W × H × D)(mm)	3064 × 1832 × 31	3064 × 1832 × 31	3674 × 2175 × 31	4894 × 2861 × 31	2678 × 1616 × 28.5	2678 × 1616 × 28.5	3344 × 1990 × 28.5	4010 × 2365 × 28.5
Weight (kg)	135	135	190	330	90	90	135	190
Resolution	1600 × 900	1920 × 1080	1920 × 1080	3840 × 2160	1280 × 720	1920 × 1080	1920 × 1080	1920 × 1080
Brightness (nits)	100–550							
Refresh Rate (Hz)	3840							
Contrast	≥6500 : 1							
Audio Frequency	Built-in 2 * 30W audio system, 2.0 channel, full frequency range							
Cabinet Material	Magnalium							
Viewing Angle (H/V)	160° /140°							
Input Port	3-way HDMI2.0 4K@60Hz Signal Input							
Picture in picture	Support HDMI 2.0 signal Picture in picture							
Installation Mode	Wall Mounting / Hanging / Mobile Stand ¹							
Maintenance	Front							
Power Consumption (Max./Ave.)(KW)	1.71/0.58	1.87/0.64	2.46/0.84	4.44/1.51	1.23/0.42	1.53/0.52	1.98/0.67	2.77/0.94
Recommended Viewing Distance(m)	≥3.8	≥3.2	≥3.8	≥2.5	≥4.2	≥2.8	≥3.5	≥4.2

1. The installation mode with mobile stand only available for 120", 138", 150", 165".

Note: Specifications are for reference only and are subject to change without notice.



Virtual Technologies Inc.

📍 :152 Bluffs Court, Canton, GA, 30114

(877)853-8478

🌐 : www.vtiusa.com

✉ : leads@vtiusa.com