



Android 16 RK3576 _ EDLA certified				
Display	Series	VT16	VT16	VT16
	Model name/number	Interactive-Flat-Panel WX-WB06527H	Interactive-Flat-Panel WX-WB07527H	Interactive-Flat-Panel WX-WB08627H
	EDLA certificate	https://storage.googleapis.com/play_public/supported_devices.html		
	Bonding	zero-gap	zero-gap	zero-gap
	Size	65 inch	75 inch	86 inch
	Panel color	Whole black	Whole black	Whole black
	Backlight	Direct	Direct	Direct
	Display area (mm)	1428.48(H)x803.52(V)	1649.664(H)*927.936(V)	1895.04(H)*1065.96(V)
	Aspect Ratio	16:9	16:9	16:9
	Viewing Angle(V/H)	178°	178°	178°
	Brightness	500nits	500nits	500nits
	Contrast ratio	5000/1	5000/1	5000/1
	Colors	1.07B(10 bits)	1.07B(10 bits)	1.07B(10 bits)
	Resolution	3840*2160	3840*2160	3840*2160
	Refresh Rate	60HZ	60HZ	60HZ
	Response time(G to G)	≤5ms	≤5ms	≤5ms
	Glass	4mm, AG+AF, tempered, Mohs7		
	Lifetime	≥50,000h	≥50,000h	≥50,000h
	Warranty	3 years	3 years	3 years
	Android	Mainboard	RK3576.B	RK3576.B
CPU		A72*4+A53*4	A72*4+A53*4	A72*4+A53*4
GPU		G52 MC3	G52 MC3	G52 MC3
RAM		8G/16G	8G/16G	8G/16G
ROM		128G/256G	128G/256G	128G/256G
Android version		16		
Touch	Touch points	40points	40points	40points
	Drawing points	20points	20points	20points
	Minimum Touch Object	2mm	2mm	2mm
	Precision	±1mm	±1mm	±1mm
Buttons	Front buttons	Eye protect/Setting/Return/Source/Home/V-/V+/Power		
Front interface	Touch-USB	1 Type-B	1 Type-B	1 Type-B
	HDMI IN(2.0)	1	1	1
	USB-C	1 X 100W	1 X 100W	1 X 100W
	USB-A	2	2	2
Rear interface	RS232	1	1	1
	Audio in(Mic in)	1	1	1
	SPDIF	1	1	1
	Audio out(Line out)	1	1	1
	RJ45 LAN in	1(1000M)	1(1000M)	1(1000M)
	RJ45 LAN out	1(1000M)	1(1000M)	1(1000M)
	Touch USB	2	2	2
	HDMI IN(1.4/2.0/2.1)	2	2	2
	DP in(1.2)	1	1	1
	Type-C	1 X 65W	1 X 65W	1 X 65W
	HDMI out(2.1)	1	1	1
	Public USB-A 3.0	2	2	2
	Android USB-A 2.0	1	1	1
	Type-C out	1	1	1
	TF slot(external)	1	1	1
OPS slot	1	1	1	

Wifi & BT	WIFI & Bluetooth	Wifi6 & BT5.2		
NFC	Multi-user	Support cards and mobile devices		
Sensor	Ambient light sensor	Support	Support	Support
Speakers	Speakers	2X20W+1X20W sub-woofer		
VESA	Standard	500*400mm	600*400mm	800*400mm
Other	Accessory	Stylus *2, Remote*1, Wall-mount*1, HDMI Cable 3M*1, NFC card*2, Touch Cable 3M*1, Power cable 3M*1, User manual*1, QC card*1		
Power consumption	Power consumption	≤105W (eco)	≤150W (eco)	≤190W (eco)
	Standby	≤0.5W	≤0.5W	≤0.5W
	Working voltage	100-240V~ 50/60Hz	100-240V~ 50/60Hz	100-240V~ 50/60Hz
Dimension	Physical dimension(mm)	1488.7*895.3*94.1	1710.8*1018.9*94.1	1957*1158.6*94.1
	Packed dimension(mm)	1626*1036*210	1848*1159*210	2094*1299*210
	NW / GW	43±1KG / 48±1KG	53±1KG / 63±1KG	67±1KG / 80±1KG